

| Model | Size | Pressure measurement range | Accuracy | Operating temperature range | Output Voltage | Supply voltage |
|--------------------------|--------------|----------------------------|-----------------|-----------------------------|----------------------|----------------|
| | [mm] | [Pa] | [% FS] Max | [°C] | [Vpp] Min. | [V] |
| TSU-20G | 87 x 40 x 22 | 0 to 200k | 0.023 | -10 to +70 | 3.2 | 12 |
| | | | | | (output load 600Ω) | |
| | | | | | Clipped sine DC cut. | |
| TSU-70G | 87 x 40 x 22 | 0 to 700k | 0.023 | -10 to +70 | 3.2 | 12 |
| | | | | | (output load 600Ω) | |
| | | | | | Clipped sine DC cut. | |
| TSU-100G | 87 x 40 x 22 | 0 to 1M | 0.023 | -10 to +70 | 3.2 | 12 |
| | | | | | (output load 600Ω) | |
| | | | | | Clipped sine DC cut. | |

| Model | Size | Nominal frequency range | Operating temperature range | Level of drive | Frequency tolerance | Frequency aging |
|-------------------------|--------|-------------------------|-----------------------------|----------------|---------------------|------------------------------------|
| | [mm] | [kHz] | [°C] | [μW] Typ. | @+25°C [%] | [V] @+25°C |
| HTS-206 | Φ2.0 | 32.4 | -40 to +85 | 0.1 | +/- 2 | ±3x10 ⁻⁶ / year Max. |