

Model	Size [ mm ]	Output wave	Output frequency range [ kHz ]	Supply voltage [ V ]	Frequency tolerance  Operating Temperature [ x10 <sup>-6</sup> / °C to °C ]
<a href="#">TG-3541CE</a> (TCXO)	3.2x2.5x1.0	CMOS	32.768	1.5 to 5.5	XA: +/-3.4 / -40 to +85
					XB: +/-5.0 / -40 to +85
					XA / XB: +/-8.0 / -40 to +105
<a href="#">TG-3541CEA</a> (TCXO) (AEC-Q100)	3.2x2.5x1.0	CMOS	32.768	1.5 to 5.5	XA: +/-3.4 / -40 to +85
					XB: +/-5.0 / -40 to +85
					XA / XB: +/-8.0 / -40 to +105
<a href="#">SG-3030CM</a>	3.2x1.5x0.9	CMOS	32.768	1.5 to 5.5	5 +/-23 / @ +25
					Ope.Temp.Range : -40 to +85
<a href="#">SG-3030LC</a>	3.6x2.8x1.2	CMOS	32.768	1.5 to 5.5	5 +/-23 / @ +25
					Ope.Temp.Range : -20 to +70
<a href="#">SG-3030JF</a>	7.1x5.1x1.5	CMOS	32.768	1.5 to 5.5	5 +/-23 / @ +25
					Ope.Temp.Range : -20 to +70
<a href="#">SG-3030JC</a>	10.5x5.8x2.7	CMOS	32.768	1.5 to 5.5	5 +/-23 / @ +25
					Ope.Temp.Range : -20 to +70
<a href="#">SG-3040LC</a>	3.6x2.8x1.2	CMOS	32.768	0.9 to 3.6	5 +/-23 / @ +25
					Ope.Temp.Range : -20 to +70
<a href="#">SG-3040JC</a>	10.5x5.8x2.7	CMOS	32.768	0.9 to 3.6	5 +/-23 / @ +25
					Ope.Temp.Range : -20 to +70